

LabScat 2

How to order?



- 1
- 2
- 3
- 4
- 5
- 6
- 7

Photometer Product variants and sets						
LabScat 2 with 50 mm cuvette			LabScat 2	Sets with 50 mm, 25 mm cuvette		
1x cuvette KPL50/190 for temperature control	1x cuvette KPL50/190	1x cuvette KPL50/190		1x cuvette KLP50/190 1x cuvette KLP25/190 Cuvette KLP 50/190 for temperature control	1x cuvette KLP50/190 1x cuvette KLP25/190	1x cuvette KLP50/190 1x cuvette KLP25/190
Cooling set +	Cooling set			Cooling set+	Cooling set	Calibration up to 500 EBC-25mm cuvette, including certificate
				Calibration up to 500 EBC-25mm cuvette, including certificate	Calibration up to 500 EBC-25mm cuvette, including certificate	Calibration up to 500 EBC-25mm cuvette, including certificate
122774	122770	122766	119185	123120	122782	122778
+ Modbus RTU	122775	122771	122763	123121	122783	122779
+ Profibus DP	122776	122772	122764	123122	122784	122780
+ Profinet IO	122777	122773	122765	123123	122785	122781

Communication

USB, Ethernet, Modbus TCP

+ Modbus RTU

+ Profibus DP

+ Profinet IO

Zubehör

- + 111786 Cuvette KPL50/190 only for LabScat with temperature control
- + 114114 Cuvette KPL50/190 glass with lock LabScat 2
- + 119468 Cuvette KLP25/190 glass with lock LabScat 2
- + 119461 Ethernet cable: LabScat 2
- + 119462 USB cable: LabScat 2
- + 112653 Water filter for LabScat 2
- + 119202 Desiccant bag, 50 g

Cooling set: Fan for cooling operation

Cooling set+: Fan for cooling operation, temperature sensor for controlling the measurement; additional required: cooling unit (E.g. Julabo Corio-CD-200F)